# EXECUTION OF PREPARATORY WORKS ON THE ARRANGEMENT OF THE CONSTRUCTION SITE FOR THE CONSTRUCTION OF THE NEW UNIVERSITY CHILDREN'S HOSPITAL TIRŠOVA 2 IN BELGRADE (PROCUREMENT NO. IOP/53-2021/UCH2)

#### Clarification no. 3

# Issued on June 08, 2021

Regarding the list of questions that the Employer, Public Investment Management Office Belgrade, No. 11 Nemanjina street, has received from the potential bidders, concerning the procurement procedure: Execution of preparatory works on the arrangement of the construction site for the construction of the new university children's hospital Tiršova 2 in Belgrade no.

# IOP/53-2021/UCH2, we give you the following answers: **Question 1:**

How many ropes are in the anchor?

#### Answer 1:

All anchors consist of wire strands 3Ø15.2mm.

# Question 2:

Exact anchor lengths (specification)?

#### Answer 2:

Specification is attached to this clarification.

# Question 3:

Exact number of anchor pieces?

#### Answer 3:

Total number of anchors is 513.

# **Question 4:**

Position 3.1 are SN anchors, depending on what is required, the tensile force that the anchor should carry must be defined?

# Answer 4:

SN anchors - steel bar yield load min 245 kN.

# Question 5:

Position no. 3.2 are temporary anchors, it is necessary to define the force, number of cables, cable diameter, length of free zone and length of tension zone.

# Answer 5:

Specification is attached to this clarification.

# Question 6:

Position 3.3. is drilling installations for 4 test anchors belong to point 3.1.

#### Answer 6:

Position 3.3 includes installation and testing of 4 test anchors, in advance of the installation of the working anchors. Fixed anchor length is 8m, free anchor length should be in accordance with the position of the selected anchor within the foundation pit. All anchors consist of wire strands 3Ø15.2mm.

Public Progurement Committee

Dragana Nenadić

# SPECIFIKACIJA ANKERA

Γ	кош	89				kom		46
	Br. užeta k	3Ø15.2				Br. užeta k		3Ø15.2
	(m)	0.5				Le Br	(m)	0.5 3/
>	(m)	7.5 (			2	-free	) (m)	7.5
		8.0 7				Lfixed Lfi		8.0 7
	7	$\dashv$			ŀ	+	-	$\dashv$
	(kN)	440				+	+	420
Н	+	360			+	+	(KN	360
- 11	- 1	2 89			- 1	takom	4	33
	Br. uzeta	3Ø15.2				Br. uzeta		3015.2
	a Œ	0.5				e .	E;	0.5
<b>=</b>	(m)	9.5			≡	Liree	E	0.5
	(m)	8.0			1	LIIXed		0.0
5	(kN)	400			7.0	777	ADD	400
7.	(kN)	200			7.4	(LAI)	360	3
100		3		ľ	moy.		17	
Rr 1170fa	3015.2	7.51		l	Rr Hžeta	7	30152	-
4		1			9	Т		1
	Ш	+		=	Lfree	(m)	9.5	
Lfixed	₩.	1			Lfixed	╀	H	
22   1	(kN) (				Z2 Lf	(kN)	410	
11								
12	360 360			L	n Z1	(kN)	360	
eta kom	3.2 60				eta kom		.2 2	
Br. užeta	3Ø15.2				Br. užeta		3Ø15.2	
Le	(E)				Le	(m)	0.5	
Lfree	(m)			-	Lfree	Œ	9.5	
Lfixed	(E) 8				Lfixed	Œ	8.0	
22	(kN)				72	(kN	410	
Z1	360				71	(KN)	360	
IZGLED 1			IZGLED 2					
			-41					

| Z1 | Z2 | Lfixed | Lfire | Le | Br. užeta | kom | (kN) | (m) | (m) | (m) | 320 | 8.0 | 9.5 | 0.5 | 3675.2 | 21 IZGLED 3

 
 Z1
 Z2
 Líree
 Le
 Br. úžeta
 kom

 (kN)
 (kN)
 (m)
 (m)
 (m)
 (m)
 360
 410
 8.0
 9.5
 0.5
 3615.2
 3
IZGLED 4

				E C				40			
	2			Br. užeta			2000	20100			
			1	e		(E	t	0.0			
			-	Lfree		Ξ	7.5	5.,			
			Lfixed		Ē	0 0	23				
			40	22		(KN)	460	3			
			7.4	17	(1.6.1)	(KIN)	360	3			
			- Low	HON			32				
		Br. užeta		חוי חלפום			3Ø15.2				
			4	1	(4)		0.5	1			
			froo	רוופפ	(w)		9.5				
			fixed	POVID	(E		8.0				
			72	1	(Z		400				
			71		2 X		360				
			Мом			1	15				
			Br. uzeta				3015.2				
		1	e	,	Ê		0.5				
-	-		Liree	17	E		9.0				
		Trees.	Lilxed	(14)	(11)	0	0.0				
		22	77	/LAIN	(NIA)	VOV	400				
		74	17	/LNI)	(NIA)	360	200				
		r mod				~	,				
		Ar 117012	DI. 02018			30152	1000				
		٥		(m)		2					
_		TIXED		E		5					
	-	X	1	(E	-	8.0					
	20	77		2×2	1	410			cini	Dí ir	
	14	7		Ž Y	000	360			zakliučavani	- randonar	Z2 - max radna sila
									71 - cila zakl	1	Z2 - max

zz - rinax radina sila Llíxed - sidrena dužina Líree - siobodna dužina Le - spoljašnja dužina ankera za prednaprezanje